Marine Physical Laboratory

AD-A231 613

Development and Testing of a Drill Hole Instrument Placement System

Final Report to Office of Naval Research Contract N00014-89-C-0009 Principal Investigator: F. N. Spiess



MPL-U-3/91 January 1991

Approved for public release; distribution unlimited.



University of California, San Diego Scripps Institution of Oceanography

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

JECOMITY COAS.				OCUMENTATIO	N PAGE			Form Approved OMB No. 0704-0188		
	REPORT SECURITY CLASSIFICATION 1b. RESTRICTIVE MARKINGS UNCLASSIFIED									
2a. SECURITY CLASSIFICATION AUTHORITY 3. DISTRIBUTION/AVAILABILITY OF REPORT										
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE				Approved for public release; distribution unlimited.						
4. PERFORMING ORGANIZATION REPORT NUMBER(S) MPL-U-3/91				5. MONITORING ORGANIZATION REPORT NUMBER(S)						
6a. NAME OF P University o				6b. OFFICE SYMBOL (If applicable) MPL	7a. NAME OF MONITORING ORGANIZATION Office of Naval Research Department of the Navy					
6c ADDRESS (C	the state of the s					ADDRESS (City, State, and ZIP Code)				
Marine Physical Laboratory Scripps Institution of Oceanography San Diego, California 92152					800 North Quincy Street Arlington, VA 22217-5000					
8a. NAME OF F ORGANIZAT		NSORING	S .	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMEN	T INSTRUMENT IDE	NTIFICA	TION NUMBER		
	Naval Res	earch		ONR	N00014-8	9-C-0009				
8c ADDRESS (Ci	ity, State, and	ZIP Cod	e)		<u></u>	UNDING NUMBERS				
800 North Quincy Street Arlington, VA 22217-5000 11. TITLE (Include Security Classification)				PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.			
11. TITLE (Includ	de Security C	lassificati	ion)		L	. I L				
DEVELOPM	MENT AND	TESTI	NG OF A	DRILL HOLE INST	TRUMENT PLAC	EMENT SYSTEM	Ī			
12. PERSONAL A	AUTHOR(S) Diess (Pr	incip	al Inves	stigator)						
13a. TYPE OF R	EPORT		36. TIME CO		14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT January 1991 2			5. PAGE COUNT 2		
16. SUPPLEMEN		ION					1			
17,	COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)						
FIELD	FIELD GROUP SUB-GROUP			wireline entry system, thruster package						
From 198 Laborate been use of a sta out loca installa array of	By through the condition and attion and four the condition.	h 199 nduct ee no 68" e simp tele ree-c R, ME	0, the 0 a pilot rthweste lectrome le reconmetry in omponent LVILLE).	end identify by block not fixed of Naval to version of a vern Atlantic DSI echanical cable inaissance logginately for geophones) from the property of the prop	Research furiteline entope sites. The and has the ing of deep omplex downhom ships of	ry system. he system is capability sea borehole ole payloads	The solution base of cases and (e.g. rese	system has ed on use arrying i for g. an		
☐ UNCLASSIFIED/UNLIMITED 🏻 SAME AS RPT. 🔲 DTIC USERS					UNCLASSIFIED 22b. TELEPHONE (Include Area Code) 22c, OFFICE SYMBOL					
F. N. Sp		מועיטאוו	UAL		(619) 534		22¢. 0	MPL		

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

Development and Testing of a Drill Hole Instrument Placement System

F. N. Spiess, (University of California, San Diego, Scripps Institution of Oceanography, A-030, La Jolla, CA 92093; 619-534-1621)

Over the last four years a pilot version of a wireline entry system has been developed and used at three northwestern Atlantic DSDP sites (417D, 418A, 534A). The system is based on use of standard 0.68" electromechanical cable and has the capability of carrying out location and simple reconnaissance logging of deep sea boreholes and for installation and telemetry involving more complex downhole payloads (e.g. an array of four three-component geophones) from ships of the academic research fleet (e.g. KNORR, MELVILLE).

In its simplest form it consists of a thruster package connected to the 0.68" wire with a logging tool suspended below it by a length of electromechanical cable appropriate to the desired downhole penetration of the tool. The thruster provides means for local control of horizontal displacement, and contains a sonar used for location of the re-entry cone during an initial lowering without the logging tool. It can interrogate and listen to the transponders in the long baseline acoustic system that provides primary ship and instrument tracking. The logging tool has a down-looking TV camera, lights, hydrophone to receive navigation signals, an upper and lower caliper, two component tilt measurement, temperature and pressure sensors. The first two deployments (holes 417 and 418) demonstrated our ability to locate the re-entry cones and to control and monitor the position, relative to the cones, of the tool hanging 200m below the thruster. In both cases, however, the holes were blocked, in the bottom of the cone, by mud of sufficient thickness to prevent the 50 kg tool from penetrating more than a few meters. Subsequent examination of the recovered sediment led to the conclusion that it had oozed up from below the casing (30m and 70m for the two holes). Hole 534 (cased to 530m) was clear, the logging tool was lowered 150m down the hole, and a proper logging pass was made up to the sea floor. To that depth the cased hole, as expected, was of uniform cross section and did not deviate from vertical by more than 1.5°. Most remarkably, the temperature just inside the hole was 4°C (ambient seawater 2°C). increasing to 8° at 150m, giving clear indication of upward flow of water in the hole. In subsequent operations a second entry was made installing a downhole geophone array and in-cone recording package described in another paper (Stephen et al.) at this meeting.

Although a number of system modifications to improve reliability and maneuverability are indicated, nevertheless, the feasibility of a simple, direct approach to the problem of hole re-entry from an oceanographic ship has been demonstrated.



ľ		_
9	ton Fer	
5	'PAŁI	
	.4 🗂	ı
,	∵ a ed □	I
3	23C10n	┨
1	·	_
		┥
	wition/	4
	bility Codes	
	will and/er	
	· Special	ı
1		١
1		İ
		ı